

Vintage Brick & Newport Brick



Vintage Brick & Newport Brick



Vintage Brick Alexandria Buff



Newport Brick Red-Buff



Newport Brick Red-Buff



Newport Brick Red-Buff



Vintage Brick White Wash



Newport Brick Rose-Red



Vintage Brick Alexandria Buff



Newport Brick Red-Red



Vintage Brick Rustic Autumn



Newport Brick Rose-Red

Fiber cement panels will not crack, rot or delaminate.

Fiber cement panels are resistant to fungus and termite infestation.

Fiber cement panels withstand extreme weather conditions.

- Classic rich brick texture for both residential and commercial applications.
- Design flexibility.
- Patented clip installation system creates a pocket of air between the panels and the substrate which reduces moisture build-up.
- Brick panels are completely compatible with vinyl, wood, metal and cellular PVC trim accessories.
- Panels are ship-lapped on four sides for tight fit and seamless appearance.
- 50-year transferable limited panel warranty*
- 15-year transferable limited finish warranty*

Product Specification

Dimensions:	Newport; Nominal 18" [h] x 6' [l] Newport; Actual 467mm [h] x 1,829mm [l] Vintage; Nominal 18" [h] x 6' [l] Vintage; Actual 455mm [h] x 1,818mm [l]
Thickness:	Nominal 3/4", Actual 18mm
Weight:	Newport; 38.75 lbs. per panel Newport; 4.5 lbs. per sq. ft. Vintage; 37.5 lbs. per panel Vintage; 4.3 lbs. per sq. ft.
Coverage:	9 sq. ft. per panel
Exposed Coverage:	9 sq. ft. per panel
Packaging:	2 panels per pack [18 sq. ft.]

Silica Dust Warning. NICHHA products contain crystalline silica (a.k.a. sand, silicon dioxide), which is a common Earth's naturally occurring mineral. Inhalation of crystalline silica into the lungs and repeated exposure, can cause health disorder, such as silicosis, lung cancer, or a potentially death. Whenever drilling, cutting, sawing, sanding or abrading the product, users must observe the following safety practices. 1) Use best work practices to reduce airborne dust concentrations. 2) Work outdoors where feasible, otherwise use mechanical ventilation. 3) Everyone handling NICHHA's product or in the vicinity of others using NICHHA's product must wear safety glasses and properly fitted respirators, prior to handling NICHHA products. We require that users wear a NIOSH/OSHA approved respirator with a rating of N100, P100, or R100 in accordance with applicable government regulations and manufacturer instructions. All employers must comply with the OSHA PEL and ACGIH TLV-TWA. 4) Use a circular saw with dust collector for cutting. The dust collector must be connected to a HEPA vacuum. 5) Do not use compressed air for cleaning dust. 6) Warn others in area. These requirements are designed to help minimize exposure to crystalline silica. We also require that you read all instructions and warnings (including the MSDS) prior to using NICHHA's product. For further information or question, please consult the MSDS or your employer. FAILURE TO ADHERE TO OUR WARNINGS, MSDS, AND OTHER INSTRUCTIONS MAY LEAD TO SERIOUS PERSONAL INJURY OR DEATH.

*See Nichiha Warranty for detailed information on terms, conditions and limitations.

*Note: Printed material may not accurately depict actual product color.

©2007 Nichiha USA, Inc. All rights reserved. Printed in the USA. 11/06 PP N1530



5855 Oakbrook Parkway,
Suite P, Norcross, GA 30093
Toll Free 1.866.Nichiha.1
(1.866.424.4421)
Phone 770.805.9466
Fax 770.805.9467

www.nichiha.com